Speaker

SS0108-19064-93P

Description



This speaker is designed to convert electrical signals into sound waves. It is commonly used in electronic devices such as smartphones, laptops, and portable speakers to produce audio output. The speaker consists of a diaphragm that vibrates in response to the electrical signals, creating sound waves that are amplified by the speaker's enclosure.

Applications

- Electronic devices
- Industrial and commercial equipment
- Home appliances
- Toys and games
- Sound effects
- Audio Alerts
- Warning Signal
- Audio Feedback

.

Electrical And Acoustical Specification

Parameter	Description
Rated Input Power.	1.0 W
Max Input Power.	1.5 W
Rated Impedance.	8Ω ± 15% & 14MH ± 4 MH
Sound Pressure Level. **(S.P.L)**	93 ± 3 dB （at0.1m/1.0W） at AVE 1.0K 1.2K 1.5K 2.0K Hz
Resonance Frequency (Fo).	750±20 % Hz
Frequency Range.	F0~20kHz.
Distortion	Less than 5% at 1KHz input Rated Power
Magnet	Rare earth permanent (NdFeB) magnet Φ9.5*1.5mm
Buzz, Rattle, etc.	Should not be audible at 2.83V sine Wave between Fo to 20KHz
Polarity	When positive voltage is applied to the terminal marked (+), diaphragm should move to the front.

Speaker


SS0108-19064-93P

Appearance	Should not exist any obstacle to be harmful to normal operation; damages, cracks, rusts and distortions, etc.
Weight.	g
Temperature	Operating temperature: -20℃ to +60℃ Storage temperature: -30℃ to +70℃

Features


Test and measurement will be carried out under normal condition of temperature within 5℃ to 35℃, relative humidity within 45% to 85% and air pressure of 860 mbar to 1060 mbar. Should uncertainly arise in data obtained from the above atmosphere, control of temperature at 20℃±2℃ and relative humidity within 60% and 70%, with air pressure remaining unchanged, to be enforced

Measuring Method




Speaker
SS0108-19064-93P


Block Diagram For Measurement Method.



Frequency Response




Environment Test

Parameter	Description
High temp. Test	Keep 96 hours at +70℃±3℃ and leave 6 hours in normal temperature and then check
Low temp. Test	Keep 96 hours at -30℃±3℃ and leave 6 hours in normal temperature and then check
Humidity test	Keep 96 hours at + 40℃±3℃ relative humidity 92-95% and leave 3 hours in normal temperature and then checked.
Temp./Humidity cycle	The part shall be subjected 5 cycles. One cycle shall be 6 hours and consist of; 
Vibration	10~55~10Hz sin-wave sweep 15min. 5G(constant) X,Y, Z 3 direction. 2 hours each, total 6 hours.
drop test	Drop the speakers contained in normal box onto the board 40 mm thick 10 times from the height of 75 cm
Load test	Rate Power white noise is applied for 96hours at room temp
Lead Wire Pull Strength	The pull force shall be applied to double lead wire： Horizontal 3.0N(0.306kg) for 30 seconds. Vertical 2.0N(0.204kg) for 30 seconds.

Speaker

SS0108-19064-93P

Dimensions




Unit:mm Tol:±0.5

The material must be meet to GU-001				
PART NO.	PART NAME	Q'TY	MATERIAL	REMARK
1	Wire	2	Black & White	1007#26
2	Diaphragm	1	PEN	
3	VOICE COIL	1	Paper+Cu	
4	Plate	1	SPCC	
5	Magnet	1	NdFeB	
6	PCB	1	FR4	
7	Frame	1	ABS	

Speaker

SS0108-19064-93P

Packing



Remark: 100 pcs per tray, 10 trays for unit, 2 units per carton

Total:2000 pcs per box

Size:34.5*26.5*29.5cm

Ordering information

Ordering can be done via www.summit-electronics.com or via info@summit-electronics.com. Please contact us for more information. Customisation of the product is available on request.

Technical support

For all product questions please contact us via info@summit-electronics.com

Document revision

Rev	Date	Changes
V01.00	06-04-2023	First issue of document