

Push Buttons

High-quality, industrial-grade, long-life panel-mount push buttons with(out) integrated LED available in latching and non-latching versions.



Dome, No illumination



Flat, No illumination



High Head, No illumination



Flat, Power Ring



Flat, Ring illumination



High Head, Ring illumination



Flat, Power Symbol



High Head, Power Symbol



Flat, Dot



High Head, Dot



Flat, No illumination



High Head, No illumination



Specifications

Size	16/19/22/25/28/30 MM
Configuration	1NO, 1NO1NC or 1NO1NC, 2NO2NC
Operation	Momentary, Latching
Temperature	-30 °C ~ + 85 °C
Protection	IP65/ IK10, IP67/IK10
Grade	3V-220V
Voltage	5A/250VAC
Switching rate	Stainless steel , Aluminum oxide brass nickel-plated, Brass chrome-plated
Material	
LED color	Green, Blue, Red, White, Yellow, RGB, Non LED, combination colors

Applications

Customization

SPB	16	-	F	R	2	-	6	M	A	-	2	0	0
Item code	Diameter options 16: 16 MM 19: 19 MM 22: 22 MM 25: 25 MM 28: 28 MM 30: 30 MM		Button Surface F: Flat H: High Head D: Dome	Illumination R: Ring Illumination P: Power Symbol D: Dot N: None	Configurations 1: 1NO 2: 1NO1NC 3: 1NO1NC, 2NO2NC		Color 0: Default 1: Green 2: Yellow 3: Blue 4: Red 5: White 6: RGB	Operation M: Momentary L: Latching	Common A: Common Anode C: Common Cathode 0: Non		Voltage 1: 3V/8V 2: 9V/24V 3: 25V/48V 4: 49V/60V 5: 110V 6: 220V		Follow number Material 0: Stainless 1: Brass Nickle 2: Brass Chrome 3: Aluminium

